

AD 2 EPBY 4-1-4

AIP POLSKA AIP POLAND

AIRAC effective date 03 JAN 2019

## STANDARD DEPARTURE CHART INSTRUMENT (SID) - ICAO

Bydgoszcz RWY 26

DESIGNATOR	ROUTE DESCRIPTION SID 11	REMARKS
INTUN 1G	Climb gradient of 5.0% is required up to FL 100 due to airspace restrictions. On RWY track to ALT 1000 ft. Turn left DCT BYZ. Turn limited to IAS 200 kt max. At BYZ turn right to intercept RDL 076 BYZ to INTUN.	SID routes requirements: - bank angle of 15°,
GOBNI 1G	Climb gradient of 5.0% is required up to FL 100 due to airspace restrictions. On RWY track to ALT 1000 ft. Turn left DCT BYZ. Turn limited to IAS 200 kt max. At BYZ turn right to intercept RDL 044 BYZ to GOBNI.	
LUXUD 1G	Climb gradient of 7.0% is required up to FL 100 due to airspace restrictions. On RWY track to ALT 1000 ft. Turn right to intercept RDL 267 BYZ to LUXUD. Turn limited to IAS 200 kt max.	ACFT unable to achieve SID profile restrictions must request non-standard departure from ATC services before start-up.